

Project Meeting
16:00 - 17:00

Menu ▶

modulEx®

Facility View – Technical Information

Features

Type: Interior

Vandalism protection: Low

Materials

The exterior cabinet is made of

- painted aluminium
- 3 mm toughened glass

Top panels are made of

- 3 mm painted aluminium
- or 3 mm phenol (for Braille or raised lettering)

Colour

Visible profiles in the cabinet are black.

The screen is set as standard to display white text on a black background. This combination can be changed if required. The same applies to the colour of the menu text and buttons.

Text

The sign is supplied with the name and/or number of the meeting room in the top right-hand corner. The text “Next meetings” can be changed if required, and the

clock in the top left-hand corner can be set to 24-hour or 12-hour display (e.g. 14.30 or 2.30 PM).

Technology

The software in Facility View is a specially developed module that is installed on the company’s server, from where all the required information is drawn – including all the activities and meetings booked in Outlook.

The technology behind the sign itself is the tried and tested Ariadne software. The sign functions as a web browser via an http protocol, and data is transferred in the same way as when a website is opened in a browser.

The system does not use an operating system, but rather “embedded software”, which ensures that the sign can be operated 24/7/365 with minimum maintenance.

Connection

The power supply and smartbox are located outside the sign. The modestly sized smartbox ensures that both data and power are supplied to the sign through the same cable.



Facility View – Technical Information

Hazardous materials

All the electronic parts in Facility View and Facility View Interactive comply with the RoHS directives. RoHS stands for “restriction on the use of certain hazardous substances in electrical and electronic equipment”. By complying with the directives this guarantees that Facility View and Facility View Interactive do not contain any hazardous substances.

Approvals

- UL 60950-1
- IEC 60950-1
- CE
- 89/336/EC

In addition, Facility View and Facility View Interactive comply with section 15 of the FCC regulations.

Warranty

We provide a 1-year production warranty on all hardware parts.


Quality

Modulæx has been awarded the ISO 9001 standard.


Environment

With a very few exceptions, all parts are made at our factory in Denmark and are therefore subject to some of the most stringent environmental requirements in the world. Moreover, in recent years we have received recognition and numerous awards for our ongoing work to minimise environmental impact and create a green, climate-friendly company.

Facility View – Assortment



35702100
Facility View 10.4" PNG sign interactive
252 x 332 mm



35701100
Facility View 10.4" PNG sign standard
252 x 332 mm



357022--
Facility View 10.4" PNG sign interactive
with header panel 252 x 56 mm
252 mm 388 mm



357012--
Facility View 10.4" PNG sign standard
with header panel 252 x 56 mm
252 mm 388 mm



357023--
Facility View 10.4" PNG sign interactive
with tactile header panel 252 x 56 mm
252 mm 388 mm



357013--
Facility View 10.4" PNG sign standard
with tactile header panel 252 x 56 mm
252 mm 388 mm